

DATASHEET

FUJITSU ESPRIMO C5730 E-STAR 5.0 DESKTOP PC

THE ULTRA SMALL PC

ESPRIMO C5730 E-STAR 5.0

The ESPRIMO C ultra small form factor PC: Enjoy maximum desktop performance and benefit from the compact design for those offices with limited space. Comfortable working - ergonomic, quiet and reliable. The sophisticated design of the ESPRIMO C provides simple and secure administration and, as a result of our made4you concept, can be easily adapted to specific customer requirements. Environmental compatibility was considered and optimized in the product development phase. This ensures that the ESPRIMO C today already meets the environmental protection requirements of tomorrow.



COMPACT DESIGN

Top quality PC for office environments with little space; also useable as a thin client.

- Ultra small form factor PC, power supply, legacy interfaces and powered serial ports integrated with a volume of only 6.9 liters

SMALL BUT EXPANDABLE

Optimal expandability despite low volume.

- Up to 500 GB hard drive and PCI Low Profile Slot

ENERGY-SAVING



Reduced power costs and consumption without any loss in performance.

- Energy-saving processor technology and power supply efficiency up to 87%.

FAMILY CONCEPT

Reduced test and evaluation costs for the existing PC infrastructure.

- Uniform technology platform and bitimage for the 5730 series from Fujitsu



COMPONENTS

PROCESSOR	Intel® Core™2 Duo processor E8600 (2C/2T, 3.33 GHz, 6 MB, 1333 MHz) Intel® Core™2 Duo processor E8500 (2C/2T, 3.16 GHz, 6 MB, 1333 MHz) Intel® Core™2 Duo processor E8400 (2C/2T, 3.0 GHz, 6 MB, 1333 MHz) Intel® Core™2 Duo processor E7600 (2C/2T, 3.06 GHz, 3 MB, 1066 MHz) Intel® Core™2 Duo processor E7500 (2C/2T, 2.93 GHz, 3 MB, 1066 MHz) Intel® Pentium® processor E6300 (2C/2T, 2.8 GHz, 2 MB, 1066 MHz) Intel® Pentium® processor E5400 (2C/2T, 2.7 GHz, 2 MB, 800 MHz) Intel® Pentium® processor E5200 (2C/2T, 2.5 GHz, 2 MB, 800 MHz) Intel® Celeron® processor E3200 (2C/2T, 2.4 GHz, 1 MB, 800 MHz)
MEMORY MODULES	1 GB (1 module(s) 1 GB) DDR2, 800 MHz, PC2-6400, DIMM 2 GB (1 module(s) 2 GB) DDR2, 800 MHz, PC2-6400, DIMM 4 GB (1 module(s) 4 GB) DDR2, 800 MHz, PC2-6400, DIMM
HARD DISK DRIVES (INTERNAL)	SSD SATA, 128 GB, 2.5-inch SATA II, 7200 rpm, 1000 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. business critical SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 320 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 250 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 160 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 160 GB, 2.5-inch, S.M.A.R.T. CF module IDE, 512 MB CF module IDE, 4 GB, (300x) CF module IDE, 1 GB
Hard disk notes	Supporting NCQ and 3 GBit CF Modules for thin client usage (with or without embedded software)
MODULAR BAY OPTIONS	DVD Super Multi, SATA I DVD Super Multi Slot-in slim, SATA
INTERFACE ADD ON CARDS/COMPONENTS (OPTIONAL)	Parallel Interface eSATA Interface Dual serial card PCI LP
Base unit	ESPRIMO C5730 E-Star5
MAINBOARD	
Mainboard type	D2804
Formfactor	proprietary
Chipset	Intel® Q43
Processor socket	LGA 775
Processor quantity maximum	1
System bus (FSB / HT / QPI)	up to 1333 MHz
Memory slots	4 DIMM (DDR2)
Supported capacity RAM (max.)	16 GB
Memory frequency	800 MHz
Memory notes	With future modules. Dual channel support. For dual channel performance, identical memory modules in each channel are necessary (minimum 2 modules).
LAN	10/100/1000 MBit/s Intel® 82567 LF
BIOS version	Phoenix 6.0
BIOS features	BIOS Flash EPROM update by software Recovery BIOS

MAINBOARD

Audio codec	Realtek ALC663
Audio features	Internal speaker supports audio playback, High Definition audio

I/O CONTROLLER ON BOARD

Serial ATA total	3
thereof eSATA	1 (optional)
Controller functions	Serial ATA II NCQ and 3 GBit AHCI

INTERFACES

Audio: line-in	1
Audio: line-out	1
USB 2.0 total	10
USB front	3
USB rear	6
USB internal	1
VGA	1
DVI	1x DVI-D
Serial (RS-232)	2 (powered, 9pi, 16 byte FIFO, 16550 compatible)
Mouse / Keyboard (PS/2)	2
Ethernet (RJ-45)	1
Parallel	optional (25pin with EPP and ECP)

INPUT DEVICE / COMPONENTS

Optical USB tilt wheel mouse
Optional: Optical USB/PS2 tilt wheel mouse

DRIVE BAYS

Drive bays total	2
3.5-inch internal bays	1
5.25-inch external bays	1
Drive bay notes	slim optical disc drive

SLOTS

PCI (32-bit / 33 MHz)	1 x (174 mm) low profile
------------------------------	--------------------------

GRAPHICS ON BOARD

Graphics brand name	Intel® GMA 4500
Shared video memory	up to 256 MB
Refresh rate 1024 x 768 (recommended / max.)	85 Hz / -
Refresh rate 1280 x 1024 (recommended / max.)	85 Hz / -
Refresh rate 1600 x 1200 (recommended / max.)	85 Hz / -
TFT resolution (VGA)	1360 x 768 pixel 1440 x 900 pixel 1680 x 1050 pixel 1920 x 1200 pixel
TFT resolution (DVI)	1360 x 768 pixel 1440 x 900 pixel 1680 x 1050 pixel 1920 x 1200 pixel
Graphics features	DirectX 10 DualView possible with DVI and VGA HDCP support
Graphics notes	Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size Resolution (color depth up to 32 Bit/pixel) For TFT we recommend using 60Hz

ELECTRICAL VALUES

Power efficiency note	power supply efficiency (at 230V; 20% / 50% / 100% load) : 82% / 87% / 87%
Rated voltage range	100 - 240 V
Rated frequency range	50 - 60 Hz
Operating voltage range	90 - 264 V
Operating line frequency range	47 - 63 Hz
Max. output of power supply	218 W
Power factor correction/active power	active
Monitor outlet	No

POWER CONSUMPTION

Power consumption note	See white paper Energy Consumption
Link to Energy White Paper	http://docs.ts.fujitsu.com/dl.aspx?id=5d0d0c1c-430c-4f21-a425-231d86d444cf

HEAT DISSIPATION

Heat dissipation notes	See white paper Energy Consumption
-------------------------------	------------------------------------

NOISE FOR STANDARD CONFIGURATION (HDD, ODD, FDD)

Noise emission	According to ISO9296
Related Processors for noise	Intel® Core™2 Duo E8600
Noise Operation mode 1: ODD load (Blue angel requirement)	4.6 B / 32 dB(A)
Noise Operation mode 2: HDD load (Blue angel requirement)	3.8 B / 23 dB(A)
Noise Operation mode 3: CPU 90% load (Blue angel requirement)	4.2 B / 27 dB(A)
Noise Operation mode 4: High load	4.2 B / 27 dB(A)
Noise Operation mode 5: Office applications	3.8 B / 22 dB(A)
Idle mode (Blue Angel requirement)	3.7 B / 22 dB(A)
Noise notes / description	A weighted sound power level Lwad (in B) / workplace related A-weighted sound pressure level LpAm (in dB(A)), Bystander position

DIMENSIONS / WEIGHT / ENVIRONMENTAL

Dimensions (W x D x H)	264 x 299 x 88 mm
Operating position	Vertical / horizontal (no feet needed)
Weight	approx. 9 kg
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	15 - 35°C

COMPLIANCE

Product	ESPRIMO C5730
Model	USD-D2804
Germany	Blauer Engel / Blue Angel GS optional
Europe	CE Nordic Swan EN 60601-1-2
USA/Canada	FCC Class B CSA
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) ENERGY STAR® 5.0 EPEAT® Silver
Compliance link	https://sp.ts.fujitsu.com/sites/certificates/default.aspx

OPERATING SYSTEM

Operating system optional preinstalled Microsoft® Windows® 7 Home Premium
Microsoft® Windows® 7 Professional
Microsoft® Windows Vista® Home Basic
Microsoft® Windows Vista® Home Premium
Microsoft® Windows Vista® Business 32-bit
Microsoft® Windows Vista® Business 64-bit
TwinLoad Microsoft® Windows® XP Professional (DVD)

Operating system compatible Linux

Operating system notes All Windows Vista® and Windows® 7 versions are Office 2007 ready.

ADDITIONAL SOFTWARE

Additional software (preinstalled) Nero Essentials S (burning software)

Additional software (optional) Recovery DVD for Windows®
Drivers & Utilities DVD (DUDVD)

COMPATIBILITY (REFERENCES)

DMI 2.0
PC 2001
WMI 1.5
USB 2.0

MANAGEABILITY

Manageability features ASF 2.0 (Alert Standard Format)
DeskUpdate Driver management
DeskView Migrate (optional)
DeskView Control (optional)
PXE 2.1 Boot code
BootP Boot Code including Bootmanage Administrator Software (tested)
Wake up from S5 (off mode)
Intrusion switch (optional)
Intel® Standard Manageability

Manageability type DeskView 10.x client management including:

DeskView features On/Offline remote client management
Detailed system inventory management and reports
BIOS Management
Remote power management
System notifications
Advanced alerts (ASF implementation)
Security Remote Control
DeskView Helpdesk Integration
WoL (Wake on LAN)

Manageability link <http://ts.fujitsu.com/manageability>
<http://www.altiris.com/fujitsu>

SECURITY

Physical security Kensington Lock support
Eye for padlock
Optional: Integrated cabinet lock

System security Boot sector virus protection
Write protect option for the Flash EPROM
Embedded security (TPM 1.2) - Infineon
Control of all USB interfaces
External USB ports can be disabled separately
Boot protection for floppy disk / CD drive and write protection for floppy disk drive
Control of external interfaces

User security User and supervisor BIOS password
SystemLock 2 BIOS SmartCard Security
Hard disk password
Optional: Access protection via external SmartCard reader
Optional: Access protection via internal SmartCard reader

SERVICEABILITY

EasyFix
EasyChange for HDD

PACKAGING INFORMATION

Packaging dimension	398x300x520 mm
Max. quantity / pallet	32
Material - Weight (g) Carton	880 g
Material - Weight (g) EPS / PS	250 g
Material - Weight (g) PE	appr. 60 g
Packaging notes	printed user documentation is bleached in chlorine free process

WARRANTY**MAINTENANCE AND SUPPORT SERVICES - THE PERFECT EXTENSION**

Recommended Service	5x9, Response Time: Next Business Day
Spare Parts availability	5 years
Service Weblink	http://ts.fujitsu.com/Supportservice

FUJITSU PLATFORM SOLUTIONS

In addition to Fujitsu ESPRIMO C5730 E-Star 5.0, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Dynamic Infrastructures

With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

MORE INFORMATION

Learn more about Fujitsu ESPRIMO C5730 E-Star 5.0, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
<http://ts.fujitsu.com/ESPRIMO>

FUJITSU GREEN POLICY INNOVATION

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT. Please find further information at <http://www.fujitsu.com/global/about/environment/>



COPYRIGHTS

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://ts.fujitsu.com/terms_of_use.html

Copyright © Fujitsu Technology Solutions

DISCLAIMER

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner

CONTACT

FUJITSU Technology Solutions
Website: <http://ts.fujitsu.com>
2010-02-01 CE-EN
